

| Wire size conductor | | structure | Insulation Thickness | Jacket Thickness | Overall Diameter | Weight | Max. Conductor resistance at 20°C | Standard Packing |
|---------------------|------|-----------|----------------------|------------------|------------------|--------|-----------------------------------|------------------|
| mm ² | AWG | NO. × mm | mm | mm | mm | Kg.Km | (Ω/km) | – |
| 2x1 re | 2x17 | 1x1.13 | 0.6 | 0.7 | 3.7x11.6 | 60 | 18.1 | Ring/coil |
| 2x1 rm | 2x17 | 7x0.42 | 0.6 | 0.7 | 3.8x11.8 | 62 | 18.1 | Ring/coil |
| 2x1.5 re | 2x16 | 1x1.35 | 0.6 | 0.7 | 3.9x12.4 | 72 | 12.1 | Ring/coil |
| 2x1.5 rm | 2x16 | 7x0.52 | 0.6 | 0.7 | 4.2x13.2 | 76 | 12.1 | Ring/coil |
| 2x2.5 re | 2x14 | 1x1.75 | 0.65 | 1 | 4.9x14 | 107 | 7.41 | Ring/coil |
| 2x2.5 rm | 2x14 | 7x0.70 | 0.65 | 1 | 5.5x15.2 | 121 | 7.41 | Ring/coil |
| 2x4 re | 2x12 | 1x2.2 | 0.85 | 1 | 5.8x16 | 150 | 4.61 | Ring/coil |
| 2x4 rm | 2x12 | 7x0.85 | 0.85 | 1 | 6.2x16.8 | 153 | 4.61 | Ring/coil |
| 3x1.5 re | 3x16 | 1x1.35 | 0.6 | 0.7 | 3.9x20.5 | 112 | 12.1 | Ring/coil |
| 3x1.5 rm | 3x16 | 7x0.52 | 0.6 | 0.7 | 4.2x21.2 | 120 | 12.1 | Ring/coil |